





Schneckenkorn SLUXX®  
(83004256)


























**2,32mm**



**0,74kg/l**

Calibration factor **1,64**

Attention! The stated settings are based on a 3kg sample test

ZA-TS / ZG-TS														
														
TSS	<b>18.0</b>	19	720	C	3	800	3	18	720	3	28	600	18	0
	<b>20.0</b>	22	900	D	X	800	1	20	900	1	30	800	19	1
	<b>21.0</b>	24	900	D	X	800	1	20	900	1	30	800	19	2
	<b>24.0</b>	32	900	D	X	800	2	20	900	2	30	800	20	4
	<b>27.0</b>	39	900	D	X	800	2	18	900	2	28	800	21	6
	<b>28.0</b>	40	900	D	X	800	2	17	900	2	27	800	21	7

Please note for your information: Even if the results of the tested fertiliser sample suggest a definitive recommendation as to the settings on the fertiliser spreader, it is not possible for AMAZONE to unequivocally guarantee the actual distribution in the field. For besides the physical properties of the fertiliser, the distribution depends on other additional factors, such as storage of the product between the testing and spreading, the setting and the level of maintenance on the spreader, or its actual operation by the tractor driver. We therefore recommend that the settings are verified in the field by the use of, for example, the mobile test kit.