











NS 27-4 Uralchem
(83010118)

 **3,65mm**

 **1,03kg/l**

Kalibreringsfaktor **1,13** Kastelengdeparameter **17,1**

ZA-TS / ZG-TS															
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
TS 1	15.0	34	600	A	1	600	1	26	500	1	36	400	19	-4	172
	16.0	35	600	A	1	600	1	25	500	1	35	400	20	-3	182
	18.0	36	600	A	1	720	1	24	600	1	34	500	20	-1	192
	20.0	35	720	A	1	720	1	23	600	1	33	500	23	-2	163
	21.0	35	720	A	1	720	1	23	600	1	33	500	23	-1	163
	24.0	42	800	A	1	800	1	22	600	1	32	500	25	-1	213
TS 2	24.0	8	600	B	3	720	3	24	600	3	34	500	27	-1	168
	27.0	9	600	D	X	500	1	22	600	1	32	500	27	1	178
	28.0	9	600	D	X	500	1	21	600	1	31	500	27	1	178
	30.0	12	720	B	3	800	3	21	720	3	31	600	31	0	167
	32.0	13	720	D	X	600	1	21	720	1	31	600	31	1	177
	33.0	13	720	D	X	600	1	20	720	1	30	600	31	2	177
	36.0	20	900	D	X	720	1	21	800	1	31	720	37	0	201
TS 3	24.0	19	900	C	1	900	1	28	720	1	38	600	21	2	190
	27.0	19	900	C	2	900	2	25	800	2	35	720	33	-5	190
	28.0	19	900	C	2	900	2	25	800	2	35	720	34	-5	190
	30.0	19	900	C	2	900	2	23	800	2	33	720	35	-5	190
	32.0	19	900	C	2	900	2	23	800	2	33	720	36	-5	191
	33.0	19	900	C	3	900	3	21	800	3	31	720	37	-4	191
	36.0	19	900	C	3	900	3	21	800	3	31	720	39	-2	191
	39.0	21	900	C	3	900	3	20	800	3	30	720	39	0	211
	40.0	21	900	D	X	720	1	19	800	1	29	720	39	0	211
	42.0	23	900	D	X	800	1	18	900	1	28	800	40	2	231
	44.0	26	900	D	X	800	1	17	900	1	27	800	41	3	259
	45.0	26	900	D	X	800	1	16	900	1	26	800	41	4	259
48.0	30	900	D	X	800	2	15	900	2	25	800	42	6	299	