



NS 30-7 Uralchem
(83008187)



3,19mm





















0,92kg/l

Kalibreringsfaktor

0,84

Kastelengdeparameter

14,6

ZA-TS / ZG-TS															
															
TS 1	15.0	23	600	A	1	720	1	25	600	1	35	500	17	-2	187
	16.0	23	600	A	1	720	1	24	600	1	34	500	17	-1	187
	18.0	27	600	A	2	720	2	23	600	2	33	500	18	0	226
	20.0	31	600	A	2	720	2	21	600	2	31	500	18	2	267
	21.0	34	600	A	2	720	2	20	600	2	30	500	18	3	297
	24.0	41	600	A+	3	720	3	19	600	3	29	500	19	5	367
TS 2	21.0	4	600	B	3	720	3	24	600	3	34	500	23	-1	200
	24.0	6	600	D	X	500	1	23	600	1	33	500	23	1	220
	27.0	13	600	D	X	500	2	21	600	2	31	500	24	3	290
	28.0	16	600	D	X	500	2	20	600	2	30	500	24	4	320
	30.0	20	720	D	X	600	2	20	720	2	30	600	27	3	286
	32.0	21	800	D	X	720	1	21	800	1	31	720	29	3	293
	33.0	23	800	D	X	720	1	20	800	1	30	720	29	4	313
TS 3	24.0	13	800	C	2	900	2	25	800	2	35	720	31	-5	211
	27.0	13	800	C	3	900	3	23	800	3	33	720	32	-4	211
	28.0	13	800	C	3	900	3	23	800	3	33	720	32	-3	211
	30.0	14	900	C	3	900	3	21	800	3	31	720	33	-3	207
	32.0	14	900	C	3	900	3	21	800	3	31	720	33	-2	207
	33.0	15	900	C	3	900	3	20	800	3	30	720	34	-1	217
	36.0	18	900	D	X	800	1	21	900	1	31	800	34	1	248
	39.0	23	900	D	X	800	1	20	900	1	30	800	35	4	298
	40.0	24	900	D	X	800	2	19	900	2	29	800	36	4	307
42.0	27	900	D	X	800	2	18	900	2	28	800	36	6	338	