





















**YaraMila 27-3-3 (UKI)**  
(83010265)

 **3,39mm**

 **1,05kg/l**

Kalibreringsfaktor **1,10** Kastelengdeparameter **16,3**

ZA-TS / ZG-TS															
															
TS 1	15.0	49	720	A	1	720	1	17	500	1	27	400	22	-5	202
	16.0	49	720	A	1	720	1	17	500	1	27	400	22	-5	202
	18.0	52	900	A	1	900	1	17	720	1	27	600	26	-5	209
	20.0	52	900	A	1	900	1	16	800	1	26	720	27	-5	209
	21.0	52	900	A	1	900	1	15	800	1	25	720	27	-5	209
	24.0	54	900	A	1	900	1	15	800	1	25	720	27	-3	229
TS 2	24.0	31	900	B	2	900	2	17	800	2	27	720	31	-5	204
	27.0	31	900	B	2	900	2	16	800	2	26	720	33	-5	204
	28.0	31	900	B	3	900	3	15	800	3	25	720	33	-4	204
	30.0	31	900	D	X	720	1	14	800	1	24	720	33	-2	204
TS 3	24.0	30	800	C	2	800	2	17	720	2	27	600	31	-5	203
	27.0	30	800	C	2	900	2	15	800	2	25	720	33	-5	203
	28.0	30	800	C	3	900	3	15	800	3	25	720	34	-5	203
	30.0	31	900	C	3	900	3	14	800	3	24	720	35	-5	198
	32.0	31	900	C	3	900	3	14	800	3	24	720	36	-4	198
	33.0	31	900	C	3	900	3	13	800	3	23	720	36	-3	198
	36.0	33	900	D	X	720	1	13	800	1	23	720	37	-1	218
	39.0	36	900	D	X	800	1	13	900	1	23	800	38	1	248
	40.0	38	900	D	X	800	1	12	900	1	22	800	38	2	268
	42.0	40	900	D	X	800	1	12	900	1	22	800	39	4	288
	44.0	42	900	D	X	800	2	11	900	2	21	800	39	5	308
	45.0	44	900	D	X	800	2	10	900	2	20	800	39	6	328
48.0	47	900	D	X	800	2	10	900	2	20	800	40	8	358	