













(83009675)

**Svavel Sour Ammoniak 21%N + 24%S
"Granmaxx"****0.76****3.25 mm****0.89 kg/l**

ZAMU									
OM 15-24	15	5 / 39	720	500	300	25	210	30	
	16	5 / 39	720	520	320	25	230	30	
	18	5 / 39	720	550	370	25	270	30	
	20	8 / 40	720	580	410	30	300	35	
	21	8 / 40	720	600	430	30	320	35	
	24	12 / 43	720	500	400	35	250	40	
	27	12 / 47	720	550	500	35	280	40	
	28	12 / 47	720	550	500	35	300	40	
OM 24-48	24	6 / 41	720	500	400	35	250	40	
	27	11 / 43	720	550	500	35	280	40	
	28	11 / 43	720	550	500	35	300	40	
	30	11 / 46	720	600	550	37	350	42	
	₁ 32	14 / 53	870	650	600	37	400	42	
	₁ 33	14 / 53	870	670	620	37	425	42	
	_{1,2} 36	16 / 55	870	720	700	37	500	42	

1. Varvtal för spridartallrik 870 r/min. 2. Monteringshöjd: a = 90 cm, b = 96 cm.



	Arbetsbredd		Kantspridning mot vattendrag
	Vinginställning		Mängdreducering i %
	Varvtal för spridartallrik		Kalibreringsfaktor
	Kant spridning		Korndiameter
	Fältkant spridning		Skakvikt

Kraftuttag	1 : 1.33	Varvtal för spridartallrik
375		500
415		550
450		600
540		720
600		800
650		870
675		900
750		1000